



45° Elbows



S × S



S × T

PART	NOMINAL SIZE	45 ELL - S × S		UNIT OF MEASURE: MM					APPROX. WT.
		D	d	d1	d2	L1	H		
0308.E45.0050	1/2"	29.50	19.00	21.54	21.23	22.50	29.50	0.03	
0308.E45.0075	3/4"	35.00	24.00	26.87	26.57	25.50	33.00	0.04	
0308.E45.0100	1"	43.00	31.00	33.65	33.27	29.00	38.50	0.07	
0308.E45.0125	1 1/4"	52.50	40.00	42.42	42.04	32.00	44.00	0.11	
0308.E45.0150	1 1/2"	59.00	46.00	48.56	48.11	35.00	48.50	0.14	
0308.E45.0200	2"	72.00	58.00	60.63	60.17	38.50	54.50	0.21	
0308.E45.0250	2 1/2"	87.50	70.00	73.38	72.85	44.50	63.00	0.36	
0308.E45.0300	3"	105.00	86.00	89.31	88.70	48.00	70.00	0.55	
0308.E45.0400	4"	132.00	110.00	114.76	114.07	57.50	85.00	0.90	
0308.E45.0500	5"	-	-	-	-	-	-	1.67	
0308.E45.0600	6"	193.00	164.00	168.83	168.00	77.00	119.50	2.65	
0308.E45.0800	8"	245.00	214.00	219.84	218.70	100.00	153.90	7.00	
0308.E45.1000	10"	318.00	-	273.81	272.67	140.00	206.30	11.00	
0308.E45.1200	12"	356.00	-	324.61	323.47	160.00	271.40	15.00	
0308.E45.1400	14"	399.00	-	356.39	-	178.00	298.60	21.00	
0308.E45.1600	16"	450.00	-	407.19	-	204.00	345.00	24.00	
0308.E45.1800	18"	505.00	-	457.99	-	228.00	381.00	32.00	
0308.E45.2000	20"	563.00	-	517.07	-	254.00	405.00	38.00	
0308.E45.2400	24"	674.00	-	611.58	-	305.00	478.00	53.00	

PART	NOMINAL SIZE	45 ELL - S × T		UNIT OF MEASURE: MM					APPROX. WT.
		D	d	d1	d2	L1	H		
N/A	1/2"	29.50	19.00	21.54	21.23	22.50	29.50	0.03	
N/A	3/4"	35.00	24.00	26.87	26.57	25.50	33.00	0.04	
N/A	1"	43.00	31.00	33.65	33.27	29.00	38.50	0.07	
N/A	1 1/4"	52.50	40.00	42.42	42.04	32.00	44.00	0.11	
N/A	1 1/2"	59.00	46.00	48.56	48.11	35.00	48.50	0.14	
N/A	2"	72.00	58.00	60.63	60.17	38.50	54.50	0.21	
N/A	2 1/2"	87.50	70.00	73.38	72.85	44.50	63.00	0.36	
N/A	3"	105.00	86.00	89.31	88.70	48.00	70.00	0.55	
N/A	4"	132.00	110.00	114.76	114.07	57.50	85.00	0.90	

Notes: Physical dimensions and tolerances meet the requirements of ASTM Standards F-439 for socket type fittings and F-437 for threaded fittings. CPVC material meets ASTM Standard D-1784. Dimensions are subject to change without notice. Contact your HYDROSEAL representative for certification.